

# Specifications

Model	
Ports	24×100Mbps PoE ports (RJ45)+2×1000Mbps Combo ports
Standards	IEEE802.3,IEEE802.3u,IEEE802.3z,IEEE802.3ab,IEEE802.3x,IEEE802.3af,IEEE802.3at,IEEE802.3az
Switching capacity	8.8Gbps
Forwarding performance	6.55Mpps
Packet Buffer	4Mbit
MAC	16K
Dimensions (W×D×H)	440mm x 207mm x 45mm(17.3"×8.1"×1.8")
Weight	<4.2kg
Power supply	AC: 100-240V, 50/60Hz
PoE	802.3at/af
Max. PoE Power	Max capacity: 370W Max capacity for single port: 30W
Switch Power	390W
Surge Protection	Common mode   ±6KV   Differential mode   ±4KV
Electrostatic standard	Common mode   ±6KV   Differential mode   ±8KV
Cooling Fans	2
Mean Time Between Failure(MTBF)	>50000 hours
Operating temperature	0°C-40°C (32°F-104°F)
Operating humidity	10%～90% (noncondensing)
Storage humidity	5%～90% (noncondensing)
Indicator	PWR: Steady on: AC input is normal Off: No AC input
	PoE: Off: No PoE power supply Steady on: PoE power supply is normal Flashing: PoE power supply is abnormal
	LINK/ACT: Off: No link Steady: Linked at 10/100Mbps Flashing: Transmitting data
	Speed: Off: Linked at 10/100Mbps On: Linked at 1000Mbps
Working Mode	Default(Normal mode) : All ports can communicate with each other. VLAN(Secure mode): Downlink ports can communicate only with uplink ports. EXTEND(Surveillance mode): Transmission distance up to 250 meters ,also downlink ports can communicate only with uplink ports.